ABHA
WALL LIGHTS

Direct | Surface



ABHA WALL LIGHTS

INPUT VOLTAGE 220-240V AC | IP66 | CRI >80

Quick Info

Mounting Type
Surface

Material Colour
Customize RAL available

Protection mode
IP66

Driver Details
Non-Dimmable/ Dali-Dimmable

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED
CCT- 2700K/ 3000K/ 4000K

CRI- ≥ 80

Life Span - L70@50000h

MacAdam - ≤3 SDCM

Beam Angle
N.A

Optics
SS/ Tuffen Glass

Efficacy
80lm/W

ABHA WALL LIGHT luminaire features a sleek, modern design crafted from stainless steel with a premium finish and toughened glass construction.

Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and CRI ≥ 80, this fixture ensures excellent color rendering and long-lasting performance. It maintains at least 70% of its luminous flux after 50,000 operating hours, guaranteeing durability and reliability over time. High-efficiency toughened glass provides uniform illumination and reduces glare.


With a standard size of 465mm Length, 200mm Width, and 120.5mm Height, this fixture is crafted for direct light distribution, making it ideal for professional exterior wall applications.

Customisations in RAL finish, wattages, and dimensions are available as per request to enhance installation and functionality.

Electrical
Wattage - 10W

Input Voltage- 220-240V AC

Single Line Diagram
Surface



Physical Dimensions
Length- 465mm

Width- 200mm

Height- 120.5mm

divinity lights

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

www.divinitylights.com