



AMANDEEP COB Spot light Downlighter is Fixed led Downlight made up of die cast aluminium housing and with premium powder coated finish.

Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency optics with beam angle options of 110° with diffuser gives uniform and zero multiple shadow illumination.

AMANDEEP

Amandeep recessed Downlighter available in 25W with Outer dia 137mm, Cutout dia 126mm, Ht 97mm, Amandeep downlighter is crafted for direct light distribution making it ideal for residential, commercial & professional applications.

Single Line Diagram

Recessed

AMANDEEP



AMANDEEP











Quick Info

Mounting Type

Recessed

Material Colour

Customize RAL avilable

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI + Power Factor (PF) -0.95 THD- <10% UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K **CRI-** > 90 **Life Span** - L70@50000h MacAdam - ≤3 SDCM

Beam Angle

110°

Optics

Opal Diffuser

Efficacy

3000K- 66.8 4000K- 74.0 5700K- 82.4 Tunable White 2700K-6500K- 74.0

Electrical

Wattage - 25W Input Voltage- 220-240 VAC

Physical

Outer Dia- 137mm Cutout Dia- 126mm Height- 97mm

