

ATLAS 75 DOWNLIGHTER

Direct | Recessed



ATLAS is IP44 rated Recessed COB Downlighter made up of die cast aluminium housing and with premium powder coated finish.

Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency optics with wide range of beam angle options of 8°, 12°, 15°, 24°, 36°, 50°, 60° creates a variety of space art atmosphere Optical structure. PMMA high luminous rate Ribbed structure lens and deep Anti Glare reflector gives uniform and shadow free illumination


ATLAS 75

Atlas 75 available in 12W with Outer Dia. 85mm, Cutout Dia. 72.5mm, Ht. 80mm, this fixture is crafted for direct light distribution making it ideal for residential, commercial & professional applications.

Options in reflector finish available as per request to enhance installation and functionality.

Single Line Diagram

Recessed



ATLAS 75 DOWNLIGHTER



Quick Info

Mounting Type

Recessed

Material Colour

Customize RAL available

Protection mode

IP44

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

8°/, 12°/, 15°/, 24°/, 36°/, 50°/, 60°

Optics

Lens

Reflector

Efficacy

3000K- 94.7

4000K- 107.2

5700K- 119.2

Tunable White 2700K-6500K- 107.2

Electrical

Wattage - 12W

Input Voltage- 220-240 VAC

Physical

Outer Dia- 85mm

Cutout Dia- 72.5mm

Height- 80mm