

CURVE SOFT 50

Direct | Recessed

CURVE SOFT 50



CURVE SOFT 50



Quick Info

Mounting Type

Recessed

Material Colour

Customize RAL available

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

110°

Optics

Opal Diffuser

Micro Prismatic Diffuser

Efficacy

3000K- 90.7

4000K- 101.9

5700K- 113.4

Tunable White 2700K-6500K- 101.9

Electrical

Wattage -28W

Opt Wattage Available- 15W/4f, 20W/4ft, 25W/4ft

Input Voltage- 220-240 VAC

Physical Dimensions

Length- 1200mm

Height- 31mm

Width- 50mm

CURVE SOFT 50 is customised sleek curved linear Luminaire with Extruded aluminium housing and with premium powder coating finish.

Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency PMMA/ Micro Prismatic diffuser provides uniform illumination

Available as per customised length, 50mm width and 31mm height, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages, Length, Shape, patterns available as per request to enhance installation and functionality.

Single Line Diagram

Recessed

