

**CURVE SOFT 85**

**divinity lights**










- LED curved linear
- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- High efficiency Micro Prismatic/ PMMA Diffuser
- Uniform illumination
- Dot-free lighting and smart arc linear
- Infinite architectural designs and circular patterns possible
- Energy efficient LED with high colour rendering
- LED PCB mounted
- For pendant or recessed mounted applications
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance

CURVE SOFT 85



CURVE SOFT 85

Product Order Code	System Power	Dimension
3022-  1	7W	L = 300mm,W = 84mm, H = 95mm
3022-  2	14W	L = 600mm,W = 84mm, H = 95mm
3022-  3	21W	L = 900mm,W = 84mm, H = 95mm
3022-  4	28W	L = 1200mm,W = 84mm, H = 95mm
3022-  5	56W	L = 2400mm,W = 84mm, H = 95mm

Order Options

Distribution






Direct

CCT (Colour Temperature)	
3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K	4




CRI	
>90	1

Beam Angle

110°

Control		
ON-OFF		1
ON-OFF (FLICKER FREE)		2
DALI-2 DT6		3
DALI-2 DT8		4
DALI +		5




Mounting Type	
Pendant	1
Recessed	2

Material Colour	
Black	
White	
Grey	

Accessories

Product Order Code	Accessories Name	Accessories Image
3022-01 	LED PCB	
3022-02	Suspension Wire	

Order Options

CCT (Colour Temperature)		
3000K		1
4000K		2
5700K		3
Tunable White 2700K-6500K		4
CRI		
>90		1