

CYLIN GLOW



Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable White 2700-6500K

ON-OFF/ ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM<3

Arcylic Diffuser

L70 @50,000h


Aluminium

Types

Pendant

Single Line Diagram

Profile



Diffuser




Colours



Light Distribution

Direct



CRI ≥ 90



TUNABLE WHITE 191

Cylin Glow

Cylin Glow fixture has

- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- High efficiency arclyic diffuser
- 280 degree uniform light distribution
- Energy efficient LED with high colour rendering
- LED PCB mounted on insert design with heat sink
- Snap-fit system and no visible screw
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance

CYLIN GLOW



CYLIN GLOW

Product Order Code	System Power	Dimension
1046-1	5W	L=300mm, Ø 32mm
1046-2	10W	L=600mm, Ø 32mm
1046-3	15W	L=900mm, Ø 32mm
1046-4	20W	L=1200mm, Ø 32mm
1046-5	40W	L=2400mm, Ø 32mm

Order Options

Distribution

Direct

CCT (Colour Temperature)

3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K	4

CRI

>90	1
-----	---

Beam Angle

280°

Control

ON-OFF		1
ON-OFF (FLICKER FREE)		2
DALI-2 DT6		3
DALI-2 DT8		4
DALI +		5

Mounting Type

Pendant	1
---------	---

Material Colour

Black	
White	
Grey	

Accessories

Product Order Code	Accessories Name	Accessories Image
1038-01 	LED PCB	
1038-02	Suspension Wire	
1038-03	Arclyic Diffuser	
1038-04	End Cap	

Order Options

CCT (Colour Temperature)		
3000K		1
4000K		2
5700K		3
Tunable White 2700K-6500K		4
CRI		
>90		1