



DISC DEEP RECESSED

Disc deep recessed fixture has:

- Aluminium Luminaire Housing
- · Deep recessed Prismatic diffuser
- · Premium Finish Powder coating
- Round frame with disc emitting a circular glow
- Direct yet diffused ambient shine
- High performance Micro Prismatic diffuser
- · Glare control & uniform light distribution
- Energy efficient LED with high colour rendering
- LED PCB mounted on insert design with heat sink
- Pendant using suspension cable with M6 bolt and fastener
- · Bottom opening for easy maintenance

divinity lights

Quick Info

CRI ≥90

3000K/ 4000K/ 5700K

Tunable white (2700K-6500K)

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8 / DALI+

SDCM<3

Micro Prismatic Diffuser

L70 @50,000h

Aluminium


Types

Pendant/Surface

Single Line Diagram

Pendant Surface





Colours








Light Distribution

Direct Direct-Indirect







F.

CRI ≥ 90

TUNABLE WHITE

divinity lights

DISC DEEP RECESSED











DISC DEEP RECESSED (DIRECT)

Product Order Code	System Power	Dimension
3002-1⊠⊚€) ■ ⊄1	35W	Ø-400mm
3002-1⊠●●■ □ 02	50W	Ø = 600mm
3002-1◘●●■□3	70W	Ø = 900mm
3002-12 ● ●	105W	Ø = 1200mm

DISC DEEP RECESSED (DIRECT-INDIRECT)

Product Order Code	System Power	Dimension
3002-▼☑⊙◐■1○1	35W	Ø-400mm
3002-▼☑◎◐■1○2	50W	Ø = 600mm
3002-▼☑◎◐■1○3	70W	Ø = 900mm
3002-▼☑◎◐▮■1○4	105W	Ø = 1200mm

Order Options

Distribution		•
Direct		1
Direct-Indirect		
Up-50% / Down-50%		2
Up-30% / Down-70%		3
Up-70% / Down-30% Up-20% / Down-80%		
CCT (Colour Temperatus	re)	1
4000K		2
5700K		3
Tunable White 2700K-6500K	2700K 6500K	4
CRI		•
>90		1
Beam Angle		
110°		
Control		
ON-OFF	<u></u>	1
ON-OFF (FLICKER FREE)	(E)	2
DALI-2 DT6	DALL	3
DALI-2 DT8	DT8	4
DALI +	DALID	5
Mounting Type		
Mounting Type Pendant		1
Pendant		
Pendant Surface	•	
Pendant Surface Material Colour	•	2

divinity lights

Accessories

Product Order Code	Accessories Name	Accessories Image
3002-01⊠●€	LED PCB	
3002-02	Suspension Wire	9
3002-03	PMMA Diffuser	
3002-04	Micro Prismatic Diffuser	

Order Options

CCT (Colour Temperature)	
3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K	4
CRI	0
>90	1