ELEVATE SINGLE HEAD
BOLLARD



CRI ≥ 80

divinity lights









ELEVATE SINGLE HEAD BOLLARD

Elevate Single Head Bollard fixture has :

· Luminaire housing of Aluminium

· IP66, High Ingress Protection against dust & moisture

· Flicker free operation for eye protection

· Energy-efficient LED with high colour rendering

· The built quality ensures long and maintenance free service life

· Optimum for every outdoor space including society parks, streets, educational institutes, and pathways

· Garden & pathway luminaires create pleasant light distribution with a high degree of visual comfort

· Sustainable LED technology offers durability and optimal light output with low power consumption

Quick Info

CRI ≥ 80

2700K, 3000K, 4000K

Non-Dimmable

SDCM<3

Clear Glass


L70 @50,000h


Aluminium Die-Cast

Type

Surface

Single Line Diagram






CRI ≥ 80

divinity lights

ELEVATE SINGLE HEAD BOLLARD



System Power	Dimensions
10W	L=148mm W=100mm H=610mm
15W	L=148mm W=100mm H=610mm
20W	L=148mm W=100mm H=610mm

Order Options

CCT (Color Temperature)

2700K

3000K

4000K

CRI

>80

Beam Angle

30°

Control

Non-Dimmable

Dali Dimmable

Mounting Type

Surface

Material Color

RAL As Per Request