



**FLEXION 95** is Premium range Recessed COB Spot light Downlighter available in Fixed and Adjustable version made up of die cast aluminium housing, heat sink and with premium powder coated finish.

Powered by high quality COB with a binning tolerance of  $\leq 3$  SDCM and CRI  $\geq 90$ . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency optics with 4 beam angle options of 12°, 24°, 36°, 50° and precision engineered, electro and nano plated reflector with 6 types reflector cover options gives uniform and zero multiple shadow illumination Flexion Downlighter available in wattage from ranging from 20W – 50W is crafted for direct light distribution making it ideal for residential & professional applications. Options in reflector cover available as per request to enhance installation and functionality.

# Single Line Diagram

Recessed

FLEXION 95



# **FLEXION 95**











# **Quick Info**

## **Mounting Type**

Recessed

#### **Material Colour**

Customize RAL avilable

#### Protection mode

IP40

### **Driver Details**

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

#### **LED**

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤3 SDCM

# **Beam Angle**

12°/, 24°/, 36°/, 50°

#### **Optics**

Lens Reflector

## Efficacy

3000K- 81.8 4000K- 91.0 5700K- 100.2 Tunable White 2700K-6500K- 91.0

## Electrical

Wattage - 20W Input Voltage- 220-240 VAC

#### **Physical**

Outer Dia- 106m
Cutout Dia- 95mm
Height-125mm

