GENISO 95 - 2x2

Direct | Pendant

GENISO 95 - 2x2

GENISO 95 - 2x2

INPUT 220-240 VAC	IP40			CRI >90

Quick Info

Mounting Type
Pendant

Material Colour
Customize RAL avilable

Protection mode
IP40

Driver Details
ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED
CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤3 SDCM

Beam Angle
110°

Optics
Opal Diffuser

Micro Prismatic Diffuser

Efficacy
3000K- 96.6

4000K- 114.0

5700K- 128.7

Tunable White 2700K-6500K- 114.0

Electrical
Wattage - 35W

Opt Wattages Available -25W/, 30W

Input Voltage- 220-240 VAC

Physical Dimension
Lenght- 595mm

Width- 595mm

Height- 95mm

**GENSIO 95 2X2** is a 2x2 feet led panel luminaire in aluminium housing and with premium powder coating finish.

Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency Micro Prismatic double diffuser provides uniform illumination and reduces glare.

With a standard size of 595 x 595 mm and with height options of 95mm this fixture is crafted for direct light distribution, making it ideal for professional applications.

Customisations in RAL finish, Wattages available as per request to enhance installation and functionality.

Single Line Diagram

Pendant

595

595