

GLOWNEST XTA ROUND 2HEAD

Direct | Recessed

GLOWNEST XTA ROUND 2HEAD



GLOWNEST XTA ROUND 2HEAD is a compact recessed downlighter designed for modern architectural and residential lighting applications. Featuring a premium lens/ XTA reflector optic system, the luminaire delivers precise and versatile illumination with beam angle options of 24°/ 36°/ and 50°. Multiple CCT options ranging from 3000K to 5700K, including Tunable White (2700K–6500K), combined with CRI ≥ 90 and MacAdam ≤ 3 SDCM, ensure excellent colour accuracy and visual comfort.



Constructed with a premium customizable RAL-finish housing, the luminaire is powered by high-quality LED technology and engineered for long-term reliability with an L70 lifetime of 50,000 hours. Compatibility with ON/OFF, DALI, and DALI-2 control protocols allows seamless integration into a variety of lighting schemes, making it suitable for hospitality, retail, residential, and commercial environments.

Its minimalist design, superior optical performance, and flexible lighting options make it an ideal solution for accent lighting, display highlighting, wall grazing, and general illumination. Designed to blend seamlessly into modern interiors, the fixture provides a refined lighting experience while enhancing architectural aesthetics. Reflector cover options are available on request to further enhance installation flexibility and functionality.

Single Line Diagram

Recessed

GLOWNEST XTA ROUND 2HEAD



GLOWNEST XTA ROUND 2HEAD



Quick Info

Mounting Type

Recessed

Material Colour

Customize RAL available

Protection mode

IP20

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI - ≥ 90

Life Span - L70@50000h

MacAdam - ≤3 SDCM

Beam Angle

24° / 36° / 50°

Optics

Lens/ Reflector

Efficacy

80lm/w

Electrical

Wattage - 4W

Input Voltage- 220-240 VAC

Physical Dimension

LXW- 70X40mm

Cutout LxW- 63.5X30.5mm

Height - 55mm