

**GOTHIC-165  
FLOOD LIGHT**

divinitylights





## GOTHIC-165

Gothic 165 Flood Light has:

- Luminaire housing of die cast- aluminium
- Surface / Spike / Clamp Mounted
- Effortless installation
- Surface powder coated
- Technology for maximum efficiency
- Tempered glass
- Zero multiple shadows
- Various beam angle range from 8° to 10X60°
- LED with effective colour rendering
- Interpretation of the real environment light
- Finned heat sinks to dissipate heat and increase performance

### Quick Info

CRI  $\geq 90$

2700K, 3000K, 4000K

Non-Dimmable/ Dali-Dimmable

SDCM<3

Clear Tempered Glass

L70 @50,000h


Aluminium Die-Cast

### Types


Surface/ Spike / Clamp

### Single Line Diagram


Surface




Spike



Clamp



### Light Distribution



CRI  $\geq 90$

GOTHIC-165



GOTHIC-165 SURFCAE MOUNTED

Product Order Code	System Power	Dimensions
1540	30W	Dia=165mm, L=163mm, H=270mm

GOTHIC-165 SPIKE MOUNTED

Product Order Code	System Power	Dimensions
1541	30W	Dia=165mm, L=228.5mm, With Spike H=539mm

GOTHIC-165 CLAMP MOUNTED

Product Order Code	System Power	Dimensions
1542	30W	Dia=165mm, L=163mm, H=230mm

Order Options

CCT (Colour Temperature)

2700K  
3000K  
4000K

CRI

>90

Beam Angle

8°  
12.5°  
20°  
30°  
60°  
15X30°  
10x60°

Control

Non-Dimmable



Dali-Dimmable



Mounting Type

Surface  
Spike  
Clamp Mounted

Material Colour

Grey

