KORNET H
BOLLARD LIGHTS

Direct | Surface




KORNET H BOLLARD LIGHT is a sleek and contemporary outdoor bollard luminaire designed with a durable aluminium housing and a compact circular head for uniform 360° illumination. Its minimalist architectural form integrates seamlessly into modern landscapes, providing comfortable and efficient lighting for garden pathways, society parks, streets, driveways, educational institutes and other outdoor spaces. The fixture features IP66 protection against dust and moisture, flicker-free LED performance and a tempered glass lens for reliable operation in outdoor environments.

With a power consumption of 12W, an efficacy of 80 lm/W and an input voltage of 24V DC, KORNET H delivers energy-efficient illumination with a service life of up to 50,000 hours (L70). Available in 2700K, 3000K and 4000K colour temperatures, with customized RAL colour options and non-dimmable or DALI-dimmable driver configurations, it offers flexibility for diverse architectural applications.

Divinity Lights provides customized lighting solutions according to clients' specific project requirements.

Single Line Diagram

Surface Mounted



KORNET H BOLLARD LIGHT

INPUT VOLTAGE 24V DC | IP66 | CRI >80

Quick Info

Mounting Type
Surface

Material Colour
Customize RAL available

Protection mode
IP66

Driver Details
Non-Dimmable, Dali Dimmable
Power Factor (PF) -0.95
THD- <10%
UGR - <19

LED
CCT- 2700K/ 3000K/ 4000K
CRI- ≥ 80
Life Span - L70@50000h
MacAdam - ≤3 SDCM

Beam Angle
360°

Optics
Lens With Tempered Glass

Efficacy
80lm/W

Electrical
Wattage - 12W
Input Voltage- 24V DC

Physical Dimensions
Dia- 207mm
Height- 50mm
Overall Height- 1049mm

divinity lights

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

www.divinitylights.com