

LUKE

divinity lights



Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable white (2700K-6500K)

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM <3

Lens & Refelctor

L70 @50,000h


Aluminium Die-cast

Types


Recessed

Single Line Diagram


LUKE 2




LUKE 3




LUKE 5



LUKE 8



LUKE 12



LUKE

Luke fixture has :


- Die cast- aluminium Luminaire housing
- Premium powder coated finish
- Round recessed spotlight
- COB (Chip on Board) technology
- Technology for maximum efficiency
- Zero multiple shadows
- LED with effective colour rendering
- Overflowing colours with soft light and shadow
- Interpretation of the real environment light and colors
- Finned heat sinks to dissipate heat and increase performance & lifespan
- High colour rendering

Colours



Light Distribution

Direct



CRI ≥ 90



TUNABLE
WHITE

LUKE



LUKE 2

Product Order Code	System Power	Dimension	Beam Angle
4016-  1	2W	Outer Dia = 30mm, Cutout Dia = 26mm, H = 24mm	15°/ 27°/ 60°

LUKE 3

Product Order Code	System Power	Dimension	Beam Angle
4016-  2	3W	Outer Dia = 40mm, Cutout Dia = 35mm, H = 30.8mm	15°/ 25°/ 50°

LUKE 5

Product Order Code	System Power	Dimension	Beam Angle
4016-  3	5W	Outer Dia = 55mm, Cutout Dia = 50mm, H = 51.4mm	15°/ 25°/ 45°

LUKE 8

Product Order Code	System Power	Dimension	Beam Angle
4016-  4	8W	Outer Dia = 65mm, Cutout Dia = 60mm, H = 61.7mm	20°/ 40°

LUKE 12

Product Order Code	System Power	Dimension	Beam Angle
4016-  5	12W	Outer Dia = 75mm, Cutout Dia = 70mm, H = 70mm	15°/ 24°/ 36°

Order Options

Distribution

Direct

CCT (Colour Temperature)	
3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K	4



CRI	
>90	1

Beam Angle

15°	1
20°	2
24°	3
25°	4
27°	5
36°	6
45°	7
50°	8
60°	9

Control		
ON-OFF		1
ON-OFF (FLICKER FREE)		2
DALI-2 DT6		3
DALI-2 DT8		4
DALI +		5

Mounting Type

Recessed

Accessories

Product Order Code	Accessories Name	Accessories Image
4016-01 	COB	

Order Options

CCT (Colour Temperature)		
3000K		1
4000K		2
5700K		3
Tunable White 2700K-6500K		4
CRI		
>90		1