

LUKE 3

Direct | Recessed



LUKE COB Downlighter is Fixed led Downlight made up of die cast aluminium housing and with premium powder coated finish.

Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency optics with beam angle options of narrow 15/20/24° to wide 45/50/60° gives uniform and zero multiple shadow illumination.

LUKE 3


Luke 3 available in 3W with Outer Dia. 40mm, Cutout Dia. 35mm, Ht. 31mm and beam angle options of 15°, 25° and 50 ° this fixture is crafted for direct light distribution making it ideal for residential & professional applications.

Options in reflector finish available as per request to enhance installation and functionality.

Single Line Diagram

Recessed

LUKE 3



LUKE 3



Quick Info

Mounting Type

Recessed

Material Colour

Customize RAL available

Protection mode

IP44

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

15°, 25°/50°

Optics

Lens

Reflector

Efficacy

3000K- 68.6

4000K- 79.7

5700K- 94.6

Tunable White 2700K-6500K- 79.7

Electrical

Wattage - 3W

Input Voltage- 220-240 VAC

Physical

Outer Dia- 40mm

Cutout Dia- 35mm

Height- 31mm