

divinity lights

LUMILINE



## Quick Info

CRI  $\geq 90$

3000K/ 4000K/ 5700K

Tunable White 2700-6500K

ON-OFF/ ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM $<3$

PMMA + Micro Prismatic Diffuser

L70 @50,000h


Aluminium

## Types

Recessed

## Single Line Diagram

Profile




## LUMILINE

Lumiline fixture has

- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- High efficiency PMMA + Micro Prismatic Diffuser
- Energy efficient LED with high colour rendering
- LED PCB mounted on insert design with heat sink
- Snap-fit system and no visible screw
- Unique curved design and patterns possible
- Bottom opening for easy maintenance

## Colours



CRI  $\geq 90$



TUNABLE WHITE



# LUMILINE



| LUMILINE                                                                                     |              |           |
|----------------------------------------------------------------------------------------------|--------------|-----------|
| Product Order Code                                                                           | System Power | Dimension |
| 1043 -  1   | 5W           | L=300mm   |
| 1043 -  2   | 10W          | L=600mm   |
| 1043 -  3 | 15W          | L=900mm   |
| 1043 -  4 | 20W          | L=1200mm  |
| 1043 -  5 | 40W          | L=2400mm  |

## Order Options

### Distribution

Direct

### CCT (Colour Temperature)

|                           |                                                                                     |   |
|---------------------------|-------------------------------------------------------------------------------------|---|
| 3000K                     |  | 1 |
| 4000K                     |                                                                                     | 2 |
| 5700K                     |                                                                                     | 3 |
| Tunable White 2700K-6500K |  | 4 |

### CRI

|     |                                                                                     |   |
|-----|-------------------------------------------------------------------------------------|---|
| >90 |  | 1 |
|-----|-------------------------------------------------------------------------------------|---|

### Beam Angle

110°

### Control

|                       |                                                                                       |                                                                                       |   |
|-----------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---|
| ON-OFF                |  |  | 1 |
| ON-OFF (FLICKER FREE) |  |                                                                                       | 2 |
| DALI-2 DT6            |  |                                                                                       | 3 |
| DALI-2 DT8            |  |                                                                                       | 4 |
| DALI +                |  |                                                                                       | 5 |

### Mounting Type

|          |                                                                                       |   |
|----------|---------------------------------------------------------------------------------------|---|
| Recessed |  | 1 |
|----------|---------------------------------------------------------------------------------------|---|

### Material Colour

|       |                                                                                       |  |
|-------|---------------------------------------------------------------------------------------|--|
| Black |  |  |
| White |  |  |
| Grey  |  |  |

Accessories

| Product Order Code                                                                        | Accessories Name         | Accessories Image                                                                    |
|-------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------|
| 1039-01  | LED PCB                  |    |
| 1039-02                                                                                   | PMMA Diffuser            |    |
| 1039-03                                                                                   | Micro Prismatic Diffuser |   |
| 1039-04                                                                                   | Profile Endcap           |  |

Order Options

| CCT (Colour Temperature)  |                                                                                     |  |
|---------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 3000K                     |                                                                                     | 1                                                                                   |
| 4000K                     |                                                                                     | 2                                                                                   |
| 5700K                     |                                                                                     | 3                                                                                   |
| Tunable White 2700K-6500K |  | 4                                                                                   |
| CRI                       |                                                                                     |  |
| >90                       |                                                                                     | 1                                                                                   |