

MICRO TREE UP LIGHT

Spike Mounted



MICRO TREE UP LIGHT is a compact outdoor LED flood luminaire in a round aluminium housing with a premium powder-coated finish.


Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and $\text{CRI} \geq 90$, the luminaire maintains at least 70% of its luminous flux after 50,000 operating hours, ensuring long-term performance and reliability. The integrated lens optic delivers a precise beam with $15^\circ / 25^\circ / 35^\circ / 45^\circ / 60^\circ$ options for uniform illumination and reduced glare.

With a compact size of 60mm Dia and 500mm height, this fixture is crafted for direct surface-mounted light distribution, making it ideal for landscape, façade, and architectural highlighting.

Customisations in RAL finish, CCT (2700K–4000K), wattages, and control options including DALI and non-dimmable versions are available upon request to enhance installation and performance flexibility.

Single Line Diagram

Spike Mounted



MICRO TREE UP LIGHT



Quick Info

Mounting Type

Spike Mounted

Material Colour

Customize RAL available

Protection mode

IP66

Driver Details

Non-Dimmable/ Dali-Dimmable

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 2700K/ 3000K/ 4000K/ RGBW

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

$15^\circ / 25^\circ / 35^\circ / 45^\circ / 60^\circ$

Optics

Lens

Efficacy

2700K- 85.2lm/W

3000K- 90.3lm/W

4000K- 95.7lm/W

Electrical

Wattage - 5W

Input Voltage- 24V DC

Physical Dimensions

Dia- 60mm

Height- 500mm