

MIDI CATENARY LIGHT

divinitylights





Quick Info

CRI ≥ 90

2700K, 3000K, 4000K

Non-Dimmable/ Dali-Dimmable

SDCM < 3

Lens






L70 @50,000h

Aluminium Die-Cast

Types

Catenary

Single Line Diagram




MIDI CATENARY LIGHT

Midi Catenary Light has:

- Luminaire housing of die cast- aluminium
- Catenary Mounted
- fixture is available in three different colour options.
 - a) Monocolour
 - b) RGB
 - c) Monocolour with decorative colourful polycarbonate shade.
- Multiple options of antiglare and decorative
- Zero multiple shadows
- Various beam angle range from 5° (Narrow) to 90° (Wide Beam)
- LED with effective colour rendering
- Interpretation of the real environment light
- Finned heat sinks to dissipate heat and increase performance

Light Distribution



CRI ≥ 90

MIDI CATENARY LIGHT



Product Order Code	System Power	Dimensions
1524	100W	Dia=290mm, Without Snoot H=250mm, With Snoot H=500mm

Order Options

CCT (Colour Temperature)

- 2700K
- 3000K
- 4000K

CRI

>90

Beam Angle

- Narrow
- Medium
- Wide

Control

- Non-Dimmable
- Dali-Dimmable



Mounting Type

Catenary

Material Colour

- Black
- Grey