

MIDI POLE LIGHT

Pole | Mounted



MIDI
POLE LIGHT

MIDI POLE LIGHT is a compact outdoor LED flood luminaire in a round aluminium housing with a premium powder-coated finish.


Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and $\text{CRI} \geq 80$, the luminaire maintains at least 70% of its luminous flux after 50,000 operating hours, ensuring long-term performance and reliability. The integrated lens optic delivers a precise beam with 8° 10° 15° 25° 30° and 50° options for uniform illumination and reduced glare.

With a compact size of 290mm Dia, and 3545mm Height, this fixture is crafted for direct light distribution, making it ideal for professional application.

Customisations in RAL finish, CCT (2700K–4000K), wattages, and control options including DALI and non-dimmable versions are available upon request to enhance installation and performance flexibility.

Single Line Diagram

Pole Mounted



MIDI POLE LIGHT



Quick Info

Mounting Type

Pole Mounted

Material Colour

Customize RAL available

Protection mode

IP66

Driver Details

Non-Dimmable/ Dali-Dimmable

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 2700K/ 3000K/ 4000K

CRI- ≥ 80

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

8° 10° 15° 25° 30° and 50°

Optics

Lens

Efficacy

80.3lm/W

Electrical

Wattage - 100W

Input Voltage- 240V AC

Physical Dimensions

Dia- 290mm

Height- 3545mm