

## MINI SHRUB LIGHT

Spike Mounted



**MINI SHRUB LIGHT** is a compact outdoor LED flood luminaire in a round aluminium housing with a premium powder-coated finish.


Powered by high-quality LEDs with a binning tolerance of  $\leq 3$  SDCM and  $\text{CRI} \geq 80$ , the luminaire maintains at least 70% of its luminous flux after 50,000 operating hours, ensuring long-term performance and reliability. The integrated lens optic delivers a precise beam with 15°/ 25°/ 35°/ 45°/ 60° options for uniform illumination and reduced glare.

With a compact size of 90mm Dia and 500mm height, this fixture is crafted for direct surface-mounted light distribution, making it ideal for landscape, façade, and architectural highlighting.

Customisations in RAL finish, CCT (2700K–4000K), wattages, and control options including DALI and non-dimmable versions are available upon request to enhance installation and performance flexibility.

### Single Line Diagram

Spike Mounted



## MINI SHRUB LIGHT



### Quick Info

#### Mounting Type

Spike Mounted

#### Material Colour

Customize RAL available

#### Protection mode

IP66

#### Driver Details

Non-Dimmable/ Dali-Dimmable

Power Factor (PF) -0.95

THD- <10%

UGR - <19

#### LED

CCT- 2700K/ 3000K/ 4000K

CRI-  $\geq 80$

Life Span - L70@50000h

MacAdam -  $\leq 3$  SDCM

#### Beam Angle

15°/ 25°/ 35°/ 45°/ 60°

#### Optics

Lens

#### Efficacy

2700K- 85.2lm/W

3000K- 90.3lm/W

4000K- 95.7lm/W

#### Electrical

Wattage - 10W

Input Voltage- 240V AC

#### Physical Dimensions

Dia- 90mm

Height- 500mm