

MINI WALL LIGHT

Wall Mounted



MINI WALL LIGHT is a compact outdoor LED flood luminaire in a round aluminium housing with a premium powder-coated finish.


Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and $\text{CRI} \geq 90$, the luminaire maintains at least 70% of its luminous flux after 50,000 operating hours, ensuring long-term performance and reliability. The integrated lens optic delivers a precise beam with narrow, medium, or wide options for uniform illumination and reduced glare.

With a compact size of 175mm Dia and 175mm height, this fixture is crafted for direct light distribution, making it ideal for professional application.

Customisations in RAL finish, CCT (2700K–4000K), wattages, and control options including DALI and non-dimmable versions are available upon request to enhance installation and performance flexibility.

Single Line Diagram

Wall Mounted



MINI WALL LIGHT



Quick Info

Mounting Type

Wall Mounted

Material Colour

Customize RAL available

Protection mode

IP66

Driver Details

Non-Dimmable/ Dali-Dimmable

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 2700K/ 3000K/ 4000K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

Narrow

Medium

Wide

Optics

Lens

Efficacy

2700K- XXXXX

3000K- XXXXX

4000K- XXXXX

Electrical

Wattage - 10W

Input Voltage- 24V DC

Physical Dimensions

Dia- 175mm

Height- 175mm