

OLEX 75 WALLWASHER

Direct | Recessed



OLEX 75 WALLWASHER COB Downlighter is Cylindrical LED Downlight made up of die cast aluminium housing, heat sink and with premium powder coated finish.

Powered by high quality COB with a binning tolerance of ≤ 3 SDCM and $\text{CRI} \geq 90$. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency optics with beam angle options of Wall washer gives uniform illumination


Olex 75 wallwasher Cylindrical Downlighter is crafted for direct light distribution making it ideal for residential, retail, hospitality & professional applications.

Customisations in RAL finish available as per request to enhance installation and functionality.

Single Line Diagram Recessed

OLEX 75WASHER

Olex Wall Washer- 75



OLEX 75 WALLWASHER



Quick Info

Mounting Type

Recessed

Material Colour

Customize RAL available

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

Wall Washer

Optics

Wall Washer

Efficacy

3000K- 83.2

4000K- 98.1

5700K- 105.9

Tunable White 2700K-6500K- 98.1

Electrical

Wattage - 13.5W

Input Voltage- 220-240 VAC

Physical

Outer Dia- 80mm

Cutout Dia- 75mm

Height- 84mm