

PALCO SMALL FLOOD LIGHT

Direct | Surface

PALCO SMALL FLOOD LIGHT




PALCO SMALL FLOOD LIGHT is a compact outdoor LED flood luminaire in a square aluminium housing with a premium powder-coated finish.

Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and $\text{CRI} \geq 80$, the luminaire maintains at least 70% of its luminous flux after 50,000 operating hours, ensuring long-term performance and reliability. The integrated lens with tempered glass optic delivers a precise beam angle with 8°/ 15°/ 25°/ 30° options for uniform illumination and reduced glare. With a compact size of 86.3mm Dia and 324mm overall height, this fixture is crafted for direct floor surface-mounted light distribution, making it ideal for landscape, façade, and architectural highlighting.

Customisations in RAL finish, CCT (2700K–5700K), wattages, and control options including DALI and non-dimmable versions are available upon request to enhance installation and performance flexibility.

Single Line Diagram

Surface



PALCO SMALL FLOOD LIGHT



Quick Info

Mounting Type

Floor Surface

Material Colour

Customize RAL available

Protection mode

IP65

Driver Details

Non-Dimmable/ Dali-Dimmable

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 2700K/ 3000K/ 4000K/ 5700K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

8°/ 15°/ 25°/ 30°

Optics

Lens with Tempered Glass

Efficacy

100lm/W

Electrical

Wattage - 30W

Input Voltage- 240V AC

Physical Dimensions

Dia- 86.3mm

Overall Height- 324mm