

PANZER



Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable white (2700K-6500K)

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM <3

Lens & Refelctor

L70 @50,000h

Aluminium Die-cast

Types

Recessed

Single Line Diagram

Recessed

PANZER 62



PANZER 90



PANZER 110



Colours



Light Distribution

Direct



CRI ≥ 90



TUNABLE WHITE



PANZER

Panzer has:

- Luminaire housing of die-cast-aluminium
- Round recessed spotlight with effortless installation
- Premium powder coated finish
- COB (Chip on Board) technology
- Fixtures for highlighting as required
- For specific areas or to accentuate a feature
- LED with effective colour rendering
- Overflowing colours with soft light and shadow
- Interpretation of the real environment light and colours
- Zero multiple shadows

PANZER



PANZER

System Power	Dimension
7W	Outer Dia- 62mm CutoutDia- 55mm Height- 62mm
10W	Outer Dia- 90mm Cutout Dia- 75mm Height- 90mm
15W	Outer Dia- 95mm Cutout Dia 110mm Height- 110mm

Order Options

CCT (Colour Temperature)

3000K

4000K

5700K

Tunable White 2700K-6500K



CRI

>90

Beam Angle

38°

Control

ON-OFF



ON-OFF (FLICKER FREE)



DALI-2 DT6



DALI-2 DT8



DALI+



Mounting

Recessed

Material Colour

RAL As Per Request