


PHOENIX DOWNLIGHTER

divinity lights



Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable white (2700K-6500K)

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM <3

Lens & Refelctor


L70 @50,000h

Aluminium Die-cast

Types

Pendant/ Surface

Single Line Diagram



Colours



Light Distribution

Direct



CRI ≥ 90



TUNABLE
WHITE

PHOENIX DOWNLIGHTER

Phoenix Downlighter has :

- Suspended & surface mounted cylindrical COB downlight
- Die cast- aluminium Luminaire housing
- Die cast heat sink
- Premium powder coated finish
- COB (Chip on Board) technology
- LED with effective colour rendering
- Efficient lens & reflector for uniform light distribution
- Vivid & accurate lighting effect
- Suitable for retail, hospitality & residential application

PHONEIX DOWNLIGHTER



PHONEIX DOWNLIGHTER

Product Order Code	System Power	Dimension
4042-  1	10W	Dia = 60mm H = 180mm
4042-  2	20W	Dia = 70mm H = 180mm
4042-  3	30W	Dia = 80mm H = 180mm
4042-  4	40W	Dia = 90mm H = 180mm

Order Options

Distribution

Direct

CCT (Colour Temperature)	
3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K	4

CRI	
>90	1

Beam Angle	
15°	1
23°	2
38°	3
55°	4

Control	
NON-Dimmable	1
DALI-2 DT6	2
DALI-2 DT8	3
DALI +	4

Mounting Type	
Pendant	1
Surface	2

Material Colour	
Black	1
White	2
Grey	3

Accessories

Product Order Code	Accessories Name	Accessories Image
4042-01   	COB	

Order Options

CCT (Colour Temperature)		
3000K		1
4000K		2
5700K		3
Tunable White 2700K-6500K		4
CRI		
>90		1