







REVA BOLLARD

Reva Bollard fixture has:

- Luminaire housing of Aluminium
- IP66, High Ingress Protection against dust & moisture
- Flicker free operation for eye protection
- Energy-efficient LED with high colour rendering
- The built quality ensures long and maintenance free service life
- Optimum for every outdoor space including society parks, streets, educational institutes, and pathways
- Garden & pathway luminaires create pleasant light distribution with a high degree of visual comfort
- $\bullet\,$ LED bollard, designed to provide radially symmetric light emission of 360°
- Sustainable LED technology offers durability and optimal light output with low power consumption

divinity lights

Quick Info

CRI ≥ 90

2700K, 3000K, 4000K

Non-Dimmable/Dali-Dimmable

SDCM<3

Clear Diffuser


L70 @50,000h


Aluminium Die-Cast


Types

Surface

Single Line Diagram







CRI ≥ 90

divinity lights

REVA BOLLARD









Product Order Code	System Power	Dimensions
1871	10W	LXW=100mmX100mm H=1000mm

Order Options

CCT (Colour Temperature)		
2700K		
3000K		
4000K		
CRI		
>90		
Beam Angle		
N.A		
Control		
Non-Dimmable	₩. William Terrent	
Dali-Dimmable		
Mounting Type		
Surface		
Material Colour		
Grey		