









RIGEL-C1 COLUMN

Rigel-C1 Column fixture has:

- Luminaire housing of Aluminium
- IP66, High Ingress Protection against dust & moisture
- Flicker free operation for eye protection
- Energy-efficient LED with high colour rendering
- The built quality ensures long and maintenance free service life
- Optimum for every outdoor space including society parks, streets, educational institutes, and pathways
- Sustainable LED technology offers durability and optimal light output with low power consumption
- Ideal design for rough outdoor environment
- Precise optics and beautiful form factor

divinity lights

Quick Info

CRI ≥ 90

2700K, 3000K, 4000K

Non-Dimmable/Dali-Dimmable

SDCM<3

Lens

L70 @50,000h

Aluminium Die-Cast


Types

Surface

Single Line Diagram







CRI ≥ 90

divinity lights

RIGEL-C1 COLUMN









| Product Order Code | System Power | Dimensions |
|--------------------|--------------|--|
| 1920 | 60W | Arm length=900mm Pole Height=3000mm |
| 1921 | 60W | Arm length=900mm Pole Height=4000mm |

Order Options

Material Colour

Grey

| CCT (Colour Temperature) | | | | |
|--------------------------|--------------|--|--|--|
| 2700K | | | | |
| 3000K | | | | |
| 4000K | | | | |
| CRI | | | | |
| >90 | | | | |
| Beam Angle | | | | |
| N.A | | | | |
| Control | | | | |
| Non-Dimmable | NOR Gimmalde | | | |
| Dali-Dimmable | | | | |
| Mounting Type | | | | |
| Surface | | | | |
| | | | | |