









RIGEL-C7 COLUMN

Rigel-C7 Column fixture has:

- Luminaire housing of Aluminium
- IP66, High Ingress Protection against dust & moisture
- Flicker free operation for eye protection
- Energy-efficient LED with high colour rendering
- The built quality ensures long and maintenance free service life
- Optimum for every outdoor space including society parks, streets, educational institutes, and pathways
- Sustainable LED technology offers durability and optimal light output with low power consumption
- Ideal design for rough outdoor environment
- Precise optics and beautiful form factor

divinity lights

Quick Info

CRI ≥ 90

2700K, 3000K, 4000K

Non-Dimmable/Dali-Dimmable

SDCM<3

Lens


L70 @50,000h

Aluminium Die-Cast

Types

Surface

Single Line Diagram





CRI ≥ 90

divinity lights

RIGEL-C7 COLUMN









Product Order Code	System Power	Dimensions
1927	2X60W	Arm length=1800mm Pole Height=6000mm

Order Options

CCT (Colour Temperature)		
2700K		
3000K		
4000K		
CRI		
>90		
Beam Angle		
N.A		
Control		
Non-Dimmable	XXX STREET, ST	
Dali-Dimmable	DAL D	
Mounting Type		
Surface		
Material Colour		
Grey		