

RING 360

Direct | Pendant



RING 360 is circular led Ring luminaire in Acrylic housing



Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency Acrylic gives uniform illumination.

FOR 630mm Disc

Available in 630mm diameter and with height options of 55.8mm, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in Wattages and Dimensions available as per request to enhance installation and functionality.

Single Line Diagram



RING 360



Quick Info

Mounting Type

Pendant

Material Colour

Customize RAL available

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

110°

Optics

Acrylic Diffuser

Efficacy

3000K- 84.0

4000K- 95.3

5700K- 108.1

Tunable White 2700K-6500K- 95.3

Electrical

Wattage -35W

Input Voltage- 220-240 VAC

Physical Dimensions

Dia- Ø630mm

Height- 55.8mm

Width- 61.5mm