

SHINE COB PRO STRIP

Direct | Surface



SHINE COB PRO STRIP Flexible LED strip lighting designed to create a smooth wash of ambient and vertical illumination between wall and ceiling planes. Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 , ensuring vibrant and accurate color rendering. The strip maintains at least 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term performance and reliability.

This flexible strip is ideal for creating dynamic, seamless lines of light in architectural spaces. Uniform illumination, tunable white options, and energy efficiency make it perfect for modern interior applications.

Customisations in wattage, color temperature, and lengths are available on request to suit specific design and installation needs.

Single Line Diagram

Surface Mounted

SHINE COB PRO STRIP



Quick Info

Mounting Type

Surface

Material Colour

Customize RAL avilable

Protection mode

IP40

Driver Details

DALI-2 DT6/ DALI-2 DT8

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- Tunable(2700K-6500K)/ (3000K-4000K)

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

110°

Optics

LED Strip

Efficacy

Tunable (3000K-4000K) - 55.7- 64.4

Tunable (2700K-6500K) - 77.7

Electrical

Wattage - 15W/Mtr

Input Voltage- 24V DC

Physical Dimensions

8mm PCB