
SHINE FLEXIBLE WALL WASHER STRIP

Direct | Surface



SHINE FLEXIBLE WALL WASHER STRIP is a high-performance, top-bend LED strip designed to deliver powerful vertical illumination along architectural surfaces. With a slim, flexible form factor, it seamlessly follows curved or linear paths, making it ideal for modern wall-washing applications. Featuring high-density LEDs with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90, it ensures uniform light output and excellent color rendering. The fixture maintains at least 70% of its luminous flux after 50,000 operating hours, ensuring long-term reliability.

Compatible with DALI-2 DT6/DT8 and flicker-free ON-OFF control, it supports advanced dimming systems. Its wide light distribution with no dark edges enhances the vertical wash effect, elevating the aesthetics of façades, corridors, and feature walls. Easy to cut, install, and mount using adhesive tape, Shine Flexible Wall Washer Strip is perfect for dynamic, surface-mounted lighting solutions.

Customisations in length, wattage, control type, and color temperature are available upon request to suit unique design and installation needs.

Single Line Diagram

Surface

SHINE FLEXIBLE WALL WASHER STRIP



Quick Info

Mounting Type

Surface

Material Colour

Customize RAL avilable

Protection mode

IP40

Driver Details

DALI-2 DT6/ DALI-2 DT8/ DMX Control

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- WW NW/ CCT/ RGB

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤3 SDCM

Beam Angle

24°

Optics

PMMA Lens (Optional optic)

Efficacy

WW NW- XXXXX

CCT-XXXXX

RGB- XXXXX

Electrical

Wattage - 18W/Mtr

Input Voltage- 24V DC

Physical Dimensions

Customize

divinity lights

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

www.divinitylights.com