

divinity lights

SHINE SPHERE



Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable White 2700-6500K

ON-OFF/ ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM<3

Lens

L70 @50,000h


Aluminium

Types

Pendant

Single Line Diagram

Profile




SHINE SPHERE

Shine Sphere fixture has

- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- High efficiency Lens
- Energy efficient LED with high colour rendering
- LED PCB mounted on insert design with heat sink
- Snap-fit system and no visible screw
- Unique curved design and patterns possible
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance

Colours



CRI ≥ 90



TUNABLE WHITE

SHINE SPHERE



SHINE SPHERE

Product Order Code	System Power	Dimension
1048 -  1	60W	L=300mm
1048 -  2	120W	L=600mm
1048 -  3	180W	L=900mm
1048 -  4	240W	L=1200mm
1048 -  5	480W	L=2400mm

Order Options

Distribution

Direct

CCT (Colour Temperature)	
3000K	☒ 1
4000K	☐ 2
5700K	☐ 3
Tunable White 2700K-6500K	 4

CRI	
>90	☒ 1

Beam Angle

25°+80° asymmetric oval beam

Control		
ON-OFF		☒ 1
ON-OFF (FLICKER FREE)		☐ 2
DALI-2 DT6		☐ 3
DALI-2 DT8		☐ 4
DALI +		☐ 5

Mounting Type	
Pendant	☒ 1

Material Colour	
Black	☒ 
White	☐ 
Grey	☐ 

Accessories

Product Order Code	Accessories Name	Accessories Image
1040-01 	LED PCB	
1040-02	Lens	
1040-03	Suspension Wire	
1040-04	End Cap	

Order Options

CCT (Colour Temperature)		
3000K	1	
4000K	2	
5700K	3	
Tunable White 2700K-6500K 	4	
CRI		
>90	1	