SHINE TUNABLE STRIP

Direct | Surface



SHINE TUNABLE STRIP Flexible LED strip lighting designed to create a smooth wash of ambient and vertical illumination between wall and ceiling planes. Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90, ensuring vibrant and accurate color rendering. The strip maintains at least 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term performance and reliability.

With a width of 9.60mm and Height of 1.95mm, this flexible strip is ideal for creating dynamic, seamless lines of light in architectural spaces. Uniform illumination, tunable white options, and energy efficiency make it perfect for modern interior applications.

Customisations in wattage, color temperature, and lengths are available on request to suit specific design and installation needs.

Single Line Diagram

Surface Mounted

SHINE TUNABLE STRIP

INPUT 220-240 VAC | IP40 | CRI >90

Quick Info

Mounting Type

Surface

Material Colour

Customize RAL avilable

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- Tunable(1800K-3000K)/ (2700K-6500K)

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤3 SDCM

Beam Angle

120^0

Optics

LED Strip

Efficacy

Tunable (1800K-3000K) - XXXXX

Tunable (2700K-6500K) - XXXXX

Electrical

Wattage - 14W

Opt Voltage Available- 15W/, 22W

Input Voltage- 24V DC

Physical Dimensions

Lenght- 1000mm

Width- 9.60mm

Height- 1.95mm

divinity lights

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

www.divinitylights.com