

SLIM RING

divinity lights



Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable white (2700K-6500K)

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM <3

PMMA Diffuser

L70 @50,000h

Aluminium

Types

Pendant

Single Line Diagram



Ø400



Ø600



Ø1000

SLIM RING

Slim Ring fixture has :


- Sleek and slim Ring with 20mm height
- Aluminium Housing
- Premium Finish Powder coating
- High efficiency PMMA diffuser
- Uninterrupted and uniform ring of LED light
- Halo of light around the ceiling
- Energy efficient LED with high colour rendering
- LED PCB mounted on insert design with heat sink
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance

Colours



Light Distribution

Direct



CRI ≥ 90



TUNABLE
WHITE

SLIM RING



SLIM RING (DIRECT)

Product Order Code	System Power	Dimension
3005- 1	30W	Ø = 400mm ,H = 20mm
3005- 2	50W	Ø = 600mm ,H = 20mm
3005- 3	70W	Ø = 1000mm ,H = 20mm

Order Options

Distribution

Direct

CCT (Colour Temperature)	
3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K	4



CRI	
>90	1

Beam Angle

110°

Control		
ON-OFF		1
ON-OFF (FLICKER FREE)		2
DALI-2 DT6		3
DALI-2 DT8		4
DALI +		5




Mounting Type

Pendant

Accessories

Product Order Code	Accessories Name	Accessories Image
3005-01 	LED PCB	
3005-02	Suspension Wire	

Order Options

CCT (Colour Temperature)		
3000K	1	
4000K	2	
5700K	3	
Tunable White 2700K-6500K 	4	
CRI		
>90	1	