

# divinity lights

### **Quick Info**

CRI ≥ 90

2700K, 3000K, 4000K

Non-Dimmable/Dali-Dimmable

SDCM<3

Clear Glass


L70 @50,000h

Aluminium Die-Cast

### **Types**

Surface

### **Single Line Diagram**











# **UNIQUE-S**


Unique-S Step light has:

- Luminaire housing of Die-Cast Aluminium
- IP65, High Ingress Protection against dust & moisture
- Extremely sustainable and requires little maintenance
- Lens optics for even light distribution
- Energy-efficient LED with high colour rendering
- Wall Light with integrated LED for orientation of pavements, stairs or terraces
- Excellent downward illumination with minimal power consumption
- Sleek & sophisticated round shape surface mounted LED light designed to elevate your outdoor lighting experience

## **Light Distribution**

Direct





CRI ≥ 90

# divinity lights

# **UNIQUE-S**









Product Order Code	System Power	Dimensions
1615	8W	LXW=215x215mm, H=36mm

# CCT (Colour Temperature) 2700K 3000K 4000K CRI >90 Beam Angle

**Order Options** 

Bealli Aligie	
60°	
Control	
Control	
Non-Dimmable	SCH Claumaide
Dali-Dimmable	DALI

<b>Mounting Type</b>	
Surface	
Material Colour	

Black	•
Grey	