







UNITY-9073

Unity-9073 Inground Light has:

- Luminaire housing of Die-Cast Aluminium
- IP67, High Ingress Protection against dust & moisture
- Ideal heat dissipation with good quality heat sink
- $\bullet~$ Beam angle narrow to wide (10° to 60°)
- COB (Chip on Board) technology
- Burial mounting
- Uniform distribution of light in the outdoor environment
- High quality toughened glass to ensure the safety of the fixture

divinity lights

Quick Info

CRI ≥ 90

2700K, 3000K, 4000K

Non-Dimmable/ Dali-Dimmable

SDCM<3

Clear Tempered Glass

L70 @50,000h


Aluminium Die-Cast

Types

Recessed


Single Line Diagram





Light Distribution





CRI ≥ 90

divinity lights

UNITY-9073









Product Order Code	System Power	Dimensions
1600	10W	L=330mm, W=90mm, H=73mm
1601	20W	L=630mm, W=90mm, H=73mm
1602	30W	L=1000mm, W=90mm, H=73mm

Order Options

CCT (Colour Temperature)

2700K

3000K

4000K

CRI

>90

Beam Angle

10°

30°

60°

Control

Non-Dimmable



Dali-Dimmable



Mounting Type

Recessed

Material Colour

Grey