
VENICE-C11
COLUMN


divinity lights











VENICE-C11 COLUMN

Venice-C11 Column fixture has :

- Luminaire housing of Aluminium
- IP66, High Ingress Protection against dust & moisture
- Flicker free operation for eye protection
- Energy-efficient LED with high colour rendering
- The built quality ensures long and maintenance free service life
- Optimum for every outdoor space including society parks, streets, educational institutes, and pathways
- Sustainable LED technology offers durability and optimal light output with low power consumption
- Ideal design for rough outdoor environment
- Precise optics and beautiful form factor

divinity lights

Quick Info

CRI ≥ 80

2700K, 3000K, 4000K

Non-Dimmable/ Dali-Dimmable

SDCM<3

PC Diffuser


L70 @50,000h


Aluminium Die-Cast

Type

Surface

Single Line Diagram






CRI ≥ 80

divinity lights

VENICE-C11 COLUMN



System Power	Dimensions
25W	LXW=100mmX100mm Pole Height=2000mm
35W	LXW=100mmX100mm Pole Height=3000mm

Order Options

CCT (Color Temperature)

2700K

3000K

4000K

CRI

>80

Beam Angle

N.A

Control

Non-Dimmable

Dali- Dimmable



Mounting Type

Surface

Material Color

RAL As Per Request