
# VENICE-C5
COLUMN LIGHTS

Direct | Surface




**VENICE-C5 COLUMN** luminaire features a sleek, architectural design crafted from durable aluminium die-cast housing with a premium powder-coated finish.


Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and CRI ≥ 80, this fixture ensures excellent color rendering and long-lasting performance. It maintains at least 70% of its luminous flux after 50,000 operating hours, ensuring reliable and energy-efficient operation. Lens + PC Diffuser construction enhances visual clarity and lighting aesthetics.

With a standard size of 2000mm Height and 100mmX100mm LXW, this fixture is designed for radial light distribution, making it ideal for every outdoor space including society parks, streets educational institutes, pathways, gardens, and outdoor applications.

Customisations in RAL finish, wattages, and height are available as per request to enhance installation and functionality.

## Single Line Diagram

Surface Mounted




**VENICE-C5** COLUMN LIGHTS




# Quick Info

### Mounting Type
Surface

### Material Colour
Customize RAL available

### Protection mode
IP66

### Driver Details
Non-Dimmable/ Dali-Dimmable

Power Factor (PF) -0.95

THD- <10%

UGR - <19

### LED
**CCT-** 2700K/ 3000K/ 4000K

**CRI-** ≥ 80

**Life Span** - L70@50000h

**MacAdam -** ≤3 SDCM

### Beam Angle
N.A

### Optics
Lens

PC Diffuser

### Efficacy
**2700K-** 80lm/W

### Electrical
**Wattage -** 30W

**Opt Wattages Available-** 20W/ 25W

**Input Voltage-** 220-240V AC

### Physical Dimensions
**LXW-** 100mmX100mm

**Pole Height-** 2000mm

divinity lights

**Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.**

www.divinitylights.com