

VERONICA WALL GRAZER

Direct | Surface



VERONICA
WALL GRAZER

VERONICA WALL GRAZER Luminaire in a sleek design with Extruded aluminium housing and with premium powder coating finish.


Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and $\text{CRI} \geq 80$, the luminaire maintains at least 70% of its luminous flux after 50,000 operating hours, ensuring long-term performance and reliability. High efficiency Lens with Tempered Glass optic delivers a precise beam 15°/ 35°/ 55° and 10X55° options for uniform illumination and reduced glare.

With a standard size of 1000mm length, 22.7mm Width, and 23.5mm Height, this fixture is crafted for direct light distribution, making it ideal for professional application.

Customisations in RAL finish, wattages, and Length available as per request to enhance installation and functionality.

Single Line Diagram

Surface Mounted



VERONICA WALL GRAZER



Quick Info

Mounting Type

Surface

Material Colour

Customize RAL available

Protection mode

IP66

Driver Details

Non-Dimmable/ Dali-Dimmable

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 2700K/ 3000K/ 4000K

CRI- ≥ 80

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

15°/ 35°/ 55°/ 10X55°

Optics

Lens with Tempered Glass

Efficacy

70lm/W

Electrical

Wattage - 10W/Mtr

Input Voltage- 240V AC

Physical Dimensions

Length- 1000mm

Width - 22.7mm

Height- 23.5mm