



**VIRAJ 45 LENS** Linear luminiare in a sleek design with a slim Extruded aluminium housing and with premium powder coating finish.

Powered by high quality LED's with a binning tolerance of  $\leq$  3 SDCM and CRI  $\geq$  90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. Deep recessed lens for better uniformty.

With a standard size of 1200mm length, 70mm height, and 46mm width, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

## **Single Line Diagram**

Pendant



## **VIRAJ 45 LENS**











# **Quick Info**

## **Mounting Type**

Pendant

## **Material Colour**

Customize RAL avilable

## **Protection mode**

IP40

## **Driver Details**

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

#### **LED**

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤3 SDCM

## **Beam Angle**

15°, 24°, 38°

#### **Optics**

<u>Lens</u>

## **Efficacy**

**3000K-** 110.1 **4000K-** 125.6 **5700K-** 141.8 **Tunable white 2700k-6500k-** 125.6

## **Electrical**

Wattage- 28W/4ft

 $\frac{\textbf{Opt Wattage Available-}\ 15W/4ft,\ 20W/4ft,\ 25W/4ft}{\textbf{Input Voltage - }220\text{-}240\ VAC}$ 

## **Physical**

Lenght- 1200 mm Height- 70 mm Width- 46 mm