

**VIRAJ 45
SQUARE**

divinity lights



Quick Info

CRI ≥90

3000K/ 4000K/ 5700K

Tunable white (2700K-6500K)

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM<3

Micro Prismatic Diffuser

L70 @50,000h





Aluminium

Types

Pendant/ Surface

Single Line Diagram

Pendant/ Surface



VIRAJ 45 SQUARE

Viraj 45 Square has :


- Square ring
- Surface powder coated
- Luminaire housing of aluminium
- LED PCB mounted
- Bottom opening for easy maintenance
- Pendant with cable suspension
- Quick mounting system
- M6 bolt for M6 fastener
- High performance Micro Prismatic Diffuser
- Uniform illumination
- Energy-efficient LED with color rendering

Colours



Light Distribution

Direct Direct-Indirect



CRI ≥ 90



TUNABLE
WHITE



VIRAJ 45 SQUARE



VIRAJ 45 SQUARE (DIRECT)

Product Order Code	System Power	Dimension
3014-1  1	35W	LXW = 600mmX600mm Profile W = 46mm, H = 70mm
3014-1  2	70W	LXW = 1200mmX1200mm Profile W = 46mm, H = 70mm
3014-1  3	105W	LXW = 2400mmX2400mm Profile W = 46mm, H = 70mm

VIRAJ 45 SQUARE (DIRECT-INDIRECT)

Product Order Code	System Power	Dimension
3014-  1	35W	LXW = 600mmX600mm Profile W = 46mm, H = 70mm
3014-  2	70W	LXW = 1200mmX1200mm Profile W = 46mm, H = 70mm
3014-  3	105W	LXW = 2400mmX2400mm Profile W = 46mm, H = 70mm

Order Options

Distribution

Direct	1
Direct-Indirect	
Up-50% / Down-50%	2
Up-30% / Down-70%	3
Up-70% / Down-30%	4
Up-20% / Down-80%	5
Up-80% / Down-20%	6

CCT (Colour Temperature)

3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K 	4

CRI

>90	1
-----	---

Beam Angle

110°	
------	--

Control

ON-OFF		1
ON-OFF (FLICKER FREE)		2
DALI-2 DT6		3
DALI-2 DT8		4
DALI +		5

Mounting Type

Pendant	1
Surface	2

Material Colour

Black		1
White		2
Grey		3

Accessories

Product Order Code	Accessories Name	Accessories Image
3014-01 	LED PCB	
3014-02	Suspension Wire	
3014-03	PMMA Diffuser	
3014-04	Prismatic Diffuser	

Order Options

CCT (Colour Temperature)	
3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K 	4
CRI	
>90	1