

VIRAJ 5690 DAISY Linear Luminaire in a sleek design with a slim Extruded aluminium housing and with premium powder coating finish.


Powered by high-quality LED's with a binning tolerance of \leq 3 SDCM and CRI \geq 90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term reliability. High efficiency lens with 3 beam angle options of 30°, 50° and widespread 80°

With a standard size of 1200 mm length, 90 mm height and 65 mm width, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages, Length and Lens + Prismatic diffuser option available as per request to enhance installation and functionality.

Single Line Diagram

Recessed



VIRAJ 5690 DAISY



Quick Info

Mounting Type

Recessed

Material Colour

Customize RAL avilable

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI + Power Factor (PF) -0.95 THD- <10% UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K CRI- ≥ 90 Life Span - L70@50000h MacAdam - ≤3 SDCM

Beam Angle

30°/ 50°/ 80°

Optics

Lens Prismatic Diffuser

Efficacy

Tunable white 2700K-6500K- 124.4	
5700K- 140.1	
4000K- 124.4	
3000K- 111.4	
2000K 111 4	

Electrical

Wattage - 28W/4ft Opt Wattages Available -15W/4ft, 20W/4ft, 25W/4ft Input Voltage- 220-240 VAC

Physical

,	
Lenght- 1200mm	
Height- 90 mm	
Width- 65 mm	

divinity lights