



VIRAJ 6090 DOUBLE DECK Linear Luminaire in a sleek design with Extruded aluminium housing and with premium powder coating finish. Unique slide-lit feature provided enhance the surroundings.


Powered by high-quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term reliability. High efficiency Prismatic double diffuser provides uniform illumination and reduces glare.

With a standard size of 1200 mm length, 90 mm height and 60 mm width, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

Single Line Diagram

Pendant



VIRAJ 6090 DOUBLE DECK











Quick Info

Mounting Type

Pendant

Material Colour

Customize RAL avilable

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI + Power Factor (PF) -0.95 THD- <10% UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K **CRI-** ≥ 90 **Life Span** - L70@50000h MacAdam - ≤3 SDCM

Beam Angle

110°

Optics

Opal Diffuser Micro Prismatic Diffuser

Efficacy

3000K- 116.8 **4000K-** 123.0 5700K-131.6 Tunable White 2700K-6500K- 123.0

Electrical

Wattage - 28W/4ft Opt Wattages Available -15W/4ft, 20W/4ft, 25W/4ft Input Voltage- 220-240 VAC

Physical

Lenght- 1200mm Height- 90 mm Width- 60 mm

