

VIRAJ DAISY MINI Linear Luminaire with a slim Extruded aluminium housing and with premium powder coating finish.


Powered by high-quality LED's with a binning tolerance of \leq 3 SDCM and CRI \geq 90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term reliability. High efficiency lens with 3 beam angle options of 30°, 40°, and widespread 65°.

With a standard size of 1200 mm length, 45 mm height and 25.5 mm width, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

Single Line Diagram

Pendant



VIRAJ DAISY MINI



Quick Info

Mounting Type

Pendant

Material Colour

Customize RAL avilable

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI + Power Factor (PF) -0.95 THD- <10% UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K CRI- ≥ 90 Life Span - L70@50000h MacAdam - ≤3 SDCM

Beam Angle

30°/ 40°/ 65°

Optics

Lens

Efficacy

,		
3000K- 115.1		
4000K- 133.2		
5700K- 148.7		
Tunable White	2700K-6500K- 133.2	

Electrical

Wattage - 25W/4ft Opt Wattages Available -10W/4ft, 15W/4ft, 20W/4ft Input Voltage- 220-240 VAC

Physical

i ily sicul		
Lenght- 1200mm		
Height- 45 mm		
Width- 25.5 mm		

divinity lights