


VIRAJ DAISY MINI

Direct | Recessed



VIRAJ DAISY MINI Linear Luminaire with a slim Extruded aluminium housing and with premium powder coating finish.


Powered by high-quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term reliability. High efficiency lens with 3 beam angle options of 30°, 40°, and widespread 65°.

With a standard size of 1200 mm length, 27mm height and 33.5 mm width, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

Single Line Diagram

Recessed



VIRAJ DAISY MINI



Quick Info

Mounting Type

Recessed

Material Colour

Customize RAL available

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

30°/ 40°/ 65°

Optics

Lens

Efficacy

3000K- 115.1

4000K- 133.2

5700K- 148.7

Tunable White 2700K-6500K- 133.2

Electrical

Wattage - 25W/4ft

Opt Wattages Available -10W/4ft, 15W/4ft, 20W/4ft

Input Voltage- 220-240 VAC

Physical

Length- 1200mm

Height- 27 mm

Width- 33.5 mm