


XTO CULTIVATOR

Direct | Surface




XTO CULTIVATOR Luminaire with Extruded aluminium housing and with premium powder coating finish and with range of size design solutions.

Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and $\text{CRI} \geq 90$. The luminaire maintains at least 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency Micro structure & antiglare optical lens design with uniform illumination and UGR less than 19.

With a standard size of 1200mm length, height of 77mm, 48mm width (**XTO 25**) this fixture is crafted for direct light distribution making it ideal for professional applications. Customisations in RAL finish, Wattages, Length and Lens + Prismatic diffuser option available as per request to enhance installation and functionality.

Single Line Diagram

Surface
XTO 25



XTO CULTIVATOR



Quick Info

Mounting Type

Surface

Material Colour

Customize RAL available

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

67°

Optics

Lens

Micro Prismatic Diffuser

Efficacy

3000K- 94.5

4000K- 105.5

5700K- 120.8

Tunable White 2700K-6500K- 105.5

Electrical

Wattage - 28W/4ft

Opt Wattages Available -15W/4ft, 20W/4ft, 25W/4ft

Input Voltage- 220-240 VAC

Physical

Length- 1200mm

Height- 77mm

Width- 48mm