

XTO CURVE SOFT

divinity lights



Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable white (2700K-6500K)

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM <3

Lens


L70 @50,000h

Aluminium

Types

Pendant/Recessed

Single Line Diagram




XTO CURVE SOFT

XTO Curve Soft has :

- LED curved slim linear
- Luminaire housing of aluminium
- Different lengths available
- Infinite architectural designs and patterns
- Uniform distribution of diffused light
- For pendant or recessed mounted applications
- Unique curved & circular patterns
- Quick mounting system
- M6 bolt for M6 fastener
- High quality flexible Neon
- Flexible & Uniform illumination
- Energy-efficient LED with color rendering

Colours



CRI ≥ 90



TUNABLE
WHITE

XTO CURVE SOFT



XTO CURVE SOFT

Product Order Code	System Power	Dimension
3017-  2	12W	L = 600mm, W = 38mm, H = 34.5mm
3017-  3	18W	L = 900mm, W = 38mm, H = 34.5mm
3017-  4	25W	L = 1200mm, W = 38mm, H = 34.5mm
3017-  5	50W	L = 2400mm, W = 38mm, H = 34.5mm

Order Options

Distribution

Direct

CCT (Colour Temperature)	
3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K	4

CRI	
>90	1

Beam Angle

67°

Control		
ON-OFF		1
ON-OFF (FLICKER FREE)		2
DALI-2 DT6		3
DALI-2 DT8		4
DALI +		5

Mounting Type	
Pendant	1
Recessed	2

Material Colour	
Black	
White	
Grey	

Accessories

Product Order Code	Accessories Name	Accessories Image
3017-01 	LED PCB	
3017-02	Suspension Wire	

Order Options

CCT (Colour Temperature)

3000K

4000K

5700K

Tunable White 2700K-6500K



1

2

3

4

CRI

1

>90