

## XTO ROUND RING

Direct | Pendant



**XTO ROUND RING** is led Ring in a sleek design with Extruded aluminium housing and with premium powder coating finish and with range of size design solutions


Powered by high quality LED's with a binning tolerance of  $\leq 3$  SDCM and CRI  $\geq 90$ . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency Micro structure & antiglare optical lens design with uniform illumination and UGR less than 16. Range of Reflector width/size and angle design available.

### For 460mm Ring


Available in 460mm diameter and with height of 76mm, this fixture is crafted for direct and uniform light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Dimensions available as per request to enhance installation and functionality.

### Single Line Diagram



XTO ROUND 460



## XTO ROUND RING



### Quick Info

#### Mounting Type

Pendant

#### Material Colour

Customize RAL available

#### Protection mode

IP40

#### Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

#### LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI-  $\geq 90$

Life Span - L70@50000h

MacAdam -  $\leq 3$  SDCM

#### Beam Angle

67°

#### Optics

Lens

#### Efficacy

3000K- 89.1

4000K- 99.6

5700K- 109.4

Tunable White 2700K-6500K- 99.6

#### Electrical

Wattage -40W

Input Voltage- 220-240 VAC

#### Physical Dimensions

Dia- Ø460mm

Height- 76mm