

XTO ROUND RING

Direct | Pendant



XTO ROUND RING is led Ring in a sleek design with Extruded aluminium housing and with premium powder coating finish and with range of size design solutions

Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency Micro structure & antiglare optical lens design with uniform illumination and UGR less than 16. Range of Reflector width/size and angle design available.


For 660mm Ring

Available in 660mm diameter and with height of 76mm, this fixture is crafted for direct and uniform light distribution making it ideal for professional applications.


Customisations in RAL finish, Wattages and Dimensions available as per request to enhance installation and functionality.

Single Line Diagram

Pendant



XTO ROUND 660



XTO ROUND RING



Quick Info

Mounting Type

Pendant

Material Colour

Customize RAL available

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

67°

Optics

Lens

Efficacy

3000K- 79.4

4000K- 87.0

5700K- 96.3

Tunable White 2700K-6500K- 87.0

Electrical

Wattage -50W

Input Voltage- 220-240 VAC

Physical Dimensions

Dia- Ø660mm

Height- 76mm