ZENEX
STREET LIGHT

divinity lights













ZENEX STREET LIGHT

Zenex Street light Fixture has :

- High grade Aluminium die-casting housing for heavy-duty outdoor
- lighting applications
- IP66 rated fixture protects from dust and harsh weather
- Flicker free operation for eye protection
- Energy-efficient LED with high colour rendering
- The built quality ensures long and maintenance free service life
- High efficiency polycarbonate UV stabilised cover with integrated
- lens to ensure symmetrical batwing light distribution
- Suitable for pole mounting
- Thermal efficient casting
- Integral heat sink design increases air flow velocity, providing maximum passive thermal management
- High quality toughened glass

divinity lights

Quick Info

CRI ≥ 80

2700K, 3000K, 4000K

Non-Dimmable/ Dali-Dimmable

SDCM<3

Tempered Glass


L70 @50,000h


Aluminium Die-Cast


Type

Pole Mounted

Single Line Diagram








Direct





CRI ≥ 80

ZENEX STREET LIGHT



System Power	Dimensions
60W	L=668mm,W=249mm H=145mm
80W	L=668mm,W=249mm H=145mm
100W	L=740mm,W=299mm H=145mm
200W	L=804mm,W=347mm H=145mm

Order Options

CCT (Color Temperature)

2700K

3000K

4000K

CRI

>80

Beam Angle

Street Optics

Control

Non-Dimmable

Dali- Dimmable

Mounting Type

Pole Mounted

Material Color

RAL code as per request